

SIEMENS



**Siemens 3 MP cameras, for clarity
that brings CCTV images to life.**

Extending the modern art of IP video surveillance

www.ssp-cctv.com

Answers for infrastructure.



CCMW3025



CFMW3025 fix-dome



CVMW3025-IR

Our latest range of 3 megapixel cameras combines classic analogue requirements and IP flexibility to satisfy the wide range of technical and operational demands of modern security environments. The H.264 & MJPEG triple-streaming functionality and ONVIF Profile S compatibility means that this range of cameras integrates easily into third-party systems.

3MP Full-HD IP Camera CCMW3025

The CCMW3025 camera comes with a number of great features as standard, and is suitable for almost any environment. It combines the requirements of analogue CCTV with the high performance, flexibility and IT security of a modern video-over-IP solution. Hybrid technology promotes the upgrade of existing video installations to a state-of-the-art IP system.

CFMW3025 fix-dome and CVMW3025-IR IP Vandal-Dome

The CFMW3025 indoor fixed dome camera and CVMW3025-IR Full HD vandal-proof IP dome camera benefits from many features, one of the key highlights is the back focus adjustment algorithm, known as 'simple auto focus' which allows commissioning and setup of back-focus via the web browser to ensure crisp video pictures day and night.

The IP66 & IK10 protection rating on the CVMW3025-IR ensures continual performance in even the roughest conditions.

Combined Features and Benefits of the 3 models include:

- Simultaneous H.264 and MJPEG encoding (triple streaming)
- Up to 3 MP resolution, supporting full HD 1080p (30 fps)
- Hybrid video: CVBS: up to 480 TVL (PAL / NTSC switchable)
- Bidirectional monaural audio
- ONVIF protocol support (Streaming Profile S compliant & Event Management)
- SNMP support for IT monitoring
- D/N with mechanical IR-cut filter

- Digital WDR functionality 57 dB
- Excellent low-light sensitivity
- Basic motion detection and tamper alarm
- Basic Acoustic Detection (Loudness threshold)
- Support SDXC up to 128 GB for local alarm recording (4 GB incl.)
- 4 user-definable privacy zones
- 5 user-definable video-cropping zones
- Integrated microphone - CCMW3025 and CFMW3025
- Lens Focal point finder algorithm - CCMW3025
- 12 V DC / 24 V AC and PoE power supply - CCMW3025 and CFMW3025
- Integrated motorised varifocal lens F1.2, 3 – 9 mm - CFMW3025 and CVMW3025-IR
- Setup of zoom and focus via web browser and one-push autofocus - CFMW3025 and CVMW3025-IR

CVMW3025-IR - specific highlights

- Vandal-proof outdoor housing design IP66 and IK10
- Integrated IR-illuminators
- 24 V AC and PoE power supply



Siemens AB
Infrastructure & Cities Sector
Building Technologies Division
Security Products
Englundavägen 7
Box 1275
17124 Solna
Sweden
Tel: +46 8 629 0300
Fax: +46 8 627 0096

Siemens AG
Infrastructure & Cities Sector
Building Technologies Division
Fire Safety and Security
Security Products
Siemensallee 84
76187 Karlsruhe,
Germany
Tel: +49 (721) 595-4291
Fax: +49 (721) 595-2806

Siemens plc
Infrastructure & Cities Sector
Building Technologies Division
Fire Safety and Security
Security Products
Suite 7
Castlegate Business Park
Caldicot
South Wales
NP26 5AD
UK
Main: +44 (0) 1291 437920
Fax: +44 (0) 1291 437943

The information in this document contains general descriptions of technical options available, which do not always have to be present in individual cases. The required features should therefore be specified in each individual case at the time of closing the contract.
©Siemens AB - 2013